



New

Wurth Super RTV Sealant Black 200ml

REF: 08933311 DEPOT: LEVENS

£20.02 + VAT

BRAND: WURTH

YEAR HOURS/MILES WEIGHT

-

High-quality adhesive and sealing compound for use in industry and the automotive sector. Excellent resistance to chemicals Can also be used in critical areas in which the seal comes into contact with various liquids. Outstanding resistance to engine oil and transmission oil, refrigerant and anti-freeze agent.

Non-acidic hardening system.

Non-corrosive, therefore has no negative impact on electronic components and on lambda probes. Sealant in compressed-air can.

Easy to dispense without additional aids. The fine beads allow the product to be applied uniformly.

Key features

NOTICE

When sealing e.g. oil pans and gearboxes it is vital that no sealant gets into the interior. For this reason we recommend to apply the sealant on a joining part surface. Join both parts and then carefully press by hand and lightly slide against each other. Afterwards separate the parts again and then remove the sealant that has gone inside. Join the components again within a max. of 5 minutes and tighten firmly. Before commissioning, observe the hardening time (depending on the sealant thickness).

LEVENS

015395 60833

Ivy House Works LA8 8PG

Unit 2, Snaygill Industrial

SKIPT(

01756 70

WASHINGTON

0191 8160991

26 Brindley Road NE37 2SB